


Load Class	(ref.. DIN EN 1433 )	A 15	B 125	C 250	D 400					For areas with occasional heavy load traffic at low speed.
Min. Quality for Bedding Concrete	(ref. DIN EN 206-1)	≥ C 12/15	≥ C 12/15	≥ C 20/25	project specific					
		( X0 )	( X0 )	( X0 )	enquiry					
Bedding Dimensions	X	≥ 10	≥ 10	≥ 15						
	Y	≥ 10	≥ 10	≥ 10						valid for the following channel systems: ( Here shown: V 100 S Typ 0.0 )
	Z	≥ 10	≥ 10	≥ 15						Multiline V100 and V150 with brickslot frame

Information contained in this drawing is copyright property of ACO Drain. Any reproduction in whole or in part without written permission of ACO Drain is prohibited. Copyright referring to DIN 34

Measurement  
cm  
Drawing-No.  
G1-E01-940-3  
Stand 12.09

Installation advice: ACO DRAIN<sup>®</sup> Channels

Surface:  
Paving



ACO SEVERIN AHLMANN  
GmbH & Co.KG  
24755 Rendsburg, P.O.Box 320  
Germany  
Tel. 0049 4331 / 354-0  
Fax 0049 4331 / 354 130  
www.aco-online.de